



V 型微通道换热器系列产品技术参数表

V Type Microchannel Heat Exchanger Parameter

| 型号 Model | 换热量(Kw) Heat Transfer | 风量(m ³ /h) Air Flow | 风机规格(mm) Fan Motor | 功率(w) Power | 进气管 Inlet (mm) | 出液管 Outlet (mm) | 安装尺寸 Installation Dimension(mm) | | | | |
|-------------|--------------------------|-----------------------------------|-----------------------|----------------|----------------------|-----------------------|------------------------------------|------|-----|------|------|
| | | | | | | | L | H | W | L1 | H1 |
| VSWTD-50 | 50 | 17440 | 550x2 | 1200 | 32 | 25 | 1320 | 1950 | 700 | 815 | 1860 |
| VSWTD-58 | 58 | 21640 | 600x2 | 1560 | 32 | 25 | 1410 | 1950 | 700 | 905 | 1860 |
| VSWTD-70 | 70 | 24400 | 630x2 | 1600 | 32 | 28 | 1600 | 2030 | 700 | 1095 | 1940 |
| VSWTD-94 | 94 | 32460 | 600x3 | 2340 | 42 | 28 | 2020 | 2030 | 700 | 1513 | 1940 |
| VSWTD-115 | 115 | 36600 | 630x3 | 2400 | 42 | 28 | 2320 | 2030 | 700 | 1815 | 1940 |

冷凝温度: 45°C

Condensing Temp.: 45°C

环境温度: 32°C

Ambient Air Temp.: 32°C

过冷度: 5°C

Sub-cooling Temp.: 5°C